1-BUTENE

Version 2.4

Chem

Product information				
	Product information			
Product Name	: 1-BUTENE			
Company	: Qatar Chemical Company LTD (QChem) Amwal Tower, Omar Al Mukhtar St, Al-Dafna (Zone 61) PO Box 24646 Doha, Qatar			
	SDS Requests: (+974) 4484-7110 Technical Information: (+974) 4476-7145 Responsible Party: Product Safety Group Email: MSDSInquiry@qchem.com.qa			
Emergency telephone:				
Asia: CHEMWATCH Mexico CHEMTREC South America SOS- Argentina: +(54)-115 EUROPE: BIG +32.1 Austria: VIZ +43 1 40 Belgium: 070 245 24 Bulgaria: +359 2 915 Croatia: +3851 2348 Cyprus: 1401 Czech Republic: Tox Denmark: Danish Po Estonia: BIG +32.14. Finland: 0800 147 11 France: ORFILA nun Germany: BIG +32.1	 9300 or 703.527.3887(int'l) +612 9186 1132) China: 0532 8388 9090 01-800-681-9531 (24 hours) Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600 839431 845455 (phone) or +32.14583516 (telefax) 643 43 (24 hours/day, 7 days/week) (24 hours/day, 7 days/week) 233 842 (24 hours/day, 7 days/week) cological Information Center +420 224 919 293, +420 224 915 402 con Center (Giftlinjen): +45 8212 1212 84545 (phone) or +32.14583516 (telefax) 1 09 471 977 (24 hours/day) ber (INRS): + 33 (0) 1 45 42 59 59 (24 hours/day, 7 days/week) .584545 (phone) or +32.14583516 (telefax) 93777 (24 hours/day, 7 days/week) -199 (24 hours/day, 7 days/week) 			

BUTENE	SAFETY DATA SHEE
ersion 2.4	Revision Date 2022-11-3
Malta: +356 2395 2000 The Netherlands: NVIC: Norway: 22 59 13 00 (24 Poland: BIG +32.14.5845 Portugal: CIAV phone nu Romania: +40213183606 Slovakia: +421 2 5477 41 Slovenia: Phone number	hours/day, 7 days/week) 545 (phone) or +32.14583516 (telefax) mber: +351 800 250 250 5 166 : 112 cy Telephone Number of Spanish Poison Centre: +34 91 562 04 20 (24
Responsible Department E-mail address Website	 Product Safety and Toxicology Group SDS@CPChem.com www.CPChem.com
ECTION 2: Hazards identificat	lion
1910.1200; the SDS and lab	 els contain all the information as required by the standard. Flammable gases, Category 1 Gases under pressure, Liquefied gas
Labeling	
Symbol(s)	
Signal Word	: Danger
Hazard Statements	
	: H220: Extremely flammable gas. H280: Contains gas under pressure; may explode if heated.
Precautionary Statements	
	 H280: Contains gas under pressure; may explode if heated. Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Response: P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 Eliminate all ignition sources if safe to do so. Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated
Precautionary Statements	 H280: Contains gas under pressure; may explode if heated. Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. Response: P377 Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 Eliminate all ignition sources if safe to do so. Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated

UTENE					
ion 2.4					Revision Date 2022-
NTP	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.				
TION 3: Composition/inform	nation	on ir	ngredients		
Synonyms	1-l Alı Bu Alı	Butyle pha-b itene	nylene ene outene -1 (C4) Butylene		
Molecular formula	: C4	4H8			
Component 1-Butene n-Butane			CAS-No. 106-98-9 106-97-8	g	Weight % 9 - 99.99 - 1
TION 4: First aid measures					
General advice			ut of dangerous a the doctor in att		w this material safety data
If inhaled		If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.			
In case of eye contact	ler	Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.			
		: Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.			
If swallowed					
	an				
TION 5: Firefighting measu	an res				
TION 5: Firefighting measu Flash point	an res : -8	i unco	onscious person.		
If swallowed TION 5: Firefighting measu Flash point Autoignition temperature Suitable extinguishing media	an res : -8 : 38	30°C ((-112°F) °C (723.00°F)	If sympto	
TION 5: Firefighting measu Flash point Autoignition temperature Suitable extinguishing	an res : -8 : 38 : Ald	30°C (33.89	(-112°F) °C (723.00°F)	If sympto	ms persist, call a physician.
TION 5: Firefighting measu Flash point Autoignition temperature Suitable extinguishing media Unsuitable extinguishing	an res : -8 : 38 : Ald : Hig	33.89 cohol	(-112°F) °C (723.00°F) -resistant foam.	If sympto	oms persist, call a physician.
TION 5: Firefighting measu Flash point Autoignition temperature Suitable extinguishing media Unsuitable extinguishing media Specific hazards during fire	an res : -8 : 38 : Ald : Hig : Sta	30°C (33.89 cohol gh vc	(-112°F) °C (723.00°F) -resistant foam. olume water jet. rd procedure for o	If sympto	oms persist, call a physician.

-BUTENE		SAFETY DATA SHEE
/ersion 2.4		Revision Date 2022-11-3
		separately in closed containments. Use a water spray to cool fully closed containers.
Fire and explosion protection	:	Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	:	Carbon oxides.
ECTION 6: Accidental release	me	asures
Personal precautions	:	Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	:	Ventilate the area.
ECTION 7: Handling and stora	ige	
Handling		
Advice on safe handling	:	For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation hood. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
Advice on protection	:	Do not spray on a naked flame or any incandescent material.
against fire and explosion		Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
		Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot
against fire and explosion	:	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot
against fire and explosion Storage Requirements for storage	: /per	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
against fire and explosion Storage Requirements for storage areas and containers	-	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.
against fire and explosion Storage Requirements for storage areas and containers ECTION 8: Exposure controls	-	Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

1-BUTENE

Version 2.4

Revision Date 2022-11-30

1	
L	15

03					
Components		Basis	Value	Control parameters	Note
1-Butene		ACGIH	TWA	250 ppm,	
n-Butane		OSHA Z-1-A	TWA	800 ppm, 1,900 mg/m3	
		ACGIH	STEL	1,000 ppm,	CNS impair, EX,
CNS impair	Central Nervous System im	pairment			
EX	Explosion hazard: the subst	ance is a flammable as	sphyxiant or excursions about	ove the TLV ® could approac	h 10% of the lower
	explosive limit.				

Immediately Dangerous to Life or Health Concentrations (IDLH)

Substance name	CAS-No.	Control parameters	Update
n-Butane	106-97-8	Immediately Dangerous to Life or Health Concentration Value 1600 parts per million	2017-02-03
		Immediately Dangerous to Life or Health Concentration Value 1600 parts per million	2017-02-03

Engineering measures

Adequate ventilation to control airborned concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection	:	If ventilation or other engineering controls are not adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure, a supplied-air NIOSH approved respirator may be appropriate. If exposure to harmful levels of airborne material may occur, a NIOSH approved respirator that provides protection may be appropriate, such as:. Air-Purifying Respirator for Organic Vapors. A positive pressure, air- supplying respirator may be appropriate if there is potential for uncontrolled release, aerosolization, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
Hand protection	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	:	Eye wash bottle with pure water. Safety glasses.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate:. Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
Hygiene measures	:	Wash hands before breaks and at the end of workday.
SDS Number:100000068454		5/15

1-BUTENE

Version 2.4

Revision Date 2022-11-30

SECTION 9: Physical and chemical properties

Form Physical state Color	 Liquefied gas, Gases under pressure Gaseous Colorless
Safety data	
Flash point	: -80°C (-112°F)
Lower explosion limit	: 1.6 %(V)
Upper explosion limit	: 9.3 %(V)
Oxidizing properties	: no
Autoignition temperature	: 383.89°C (723.00°F)
Molecular formula	: C4H8
Molecular weight	: 56.12 g/mol
рН	: Not applicable
Freezing point	: -185°C (-301°F)
Pour point	No data available
Boiling point/boiling range	: -6.26°C (20.73°F)
Vapor pressure	: 1,895.00 MMHG at 20°C (68°F)
Relative density	: 0.6 at 15.6 °C (60.1 °F)
Density	: 600.3 g/l
Water solubility	: Soluble in hydrocarbon solvents; insoluble in water.
Partition coefficient: n-	: No data available
octanol/water Viscosity, kinematic	: No data available
Relative vapor density	: 1.93 (Air = 1.0)
Evaporation rate	: No data available
Percent volatile	: > 99 %

1-BUTENE

Version 2.4

Reactivity	: Stable at normal ambient temperature and pressure.
Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous rea	ctions
Hazardous reactions	: Hazardous reactions: Hazardous polymerization does not occur.
	Further information: No decomposition if stored and applied as directed.
	Hazardous reactions: Vapors may form explosive mixture with air.
Conditions to avoid	: Heat, sparks, fire, and oxidizing agents. Heat, flames and sparks.
Materials to avoid Hazardous decomposition	 May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc. Carbon oxides
products	. Carbon oxides
Other data	: No decomposition if stored and applied as directed.
TION 11: Toxicological infor	mation
1-BUTENE Acute oral toxicity	: Negligible or unlikely exposure pathways
1-BUTENE Acute inhalation toxicity	 LC50: > 10000 ppm Exposure time: 4 h Species: Rat Test atmosphere: vapor Method: OECD Test Guideline 403 Information given is based on data obtained from similar substances.
1-BUTENE Acute dermal toxicity	: Negligible or unlikely exposure pathways
1-BUTENE Skin irritation	: No skin irritation. Rapid evaporation of the liquid may cause frostbite.
Number:100000068454	7/15

1-BUTENE

Version 2.4

SAFETY DATA SHEET

1-BUTENE Eye irritation	: No eye irritation. Contact with liquid or refrigerated gas can cause cold burns and frostbite.
1-BUTENE Sensitization	: No data available.
Repeated dose toxicity	
1-Butene	 Species: Rat, Male and female Sex: Male and female Application Route: Inhalation Dose: 0, 500, 2000, 8000 ppm Exposure time: 28 d Number of exposures: 6 hr/d, 7 d/wk NOEL: 8000 ppm Method: OECD Guideline 422 No adverse effect has been observed in chronic toxicity tests
n-Butane	Species: Rat, Male and female Sex: Male and female Application Route: Inhalation Dose: 0, 1017, 4489 ppm Exposure time: 90 day Number of exposures: 6 hr/d, 5 d/wk NOEL: 4489 ppm
Genotoxicity in vitro	
1-Butene	: Test Type: Ames test Metabolic activation: with and without metabolic activation Result: negative
n-Butane	Test Type: Ames test Result: negative
Genotoxicity in vivo	
1-Butene	: Test Type: Micronucleus test Species: Mouse Dose: 1000, 3260, 10000 ppm Method: Mutagenicity (micronucleus test) Result: negative
Carcinogenicity	
1-Butene	 Species: Rat Sex: male Dose: 0, 500, 2000, 8000 ppm Exposure time: 2 years Number of exposures: 6 hr/d, 5 d/wk Remarks: increased incidence of thyroid tumors, Information given is based on data obtained from similar substances.

1-BUTENE

rsion 2.4	Revision Date 2022-11
	Species: Rat Sex: female Dose: 0, 500, 2000, 8000 ppm Exposure time: 2 years Number of exposures: 6 hr/d, 5 d/wk Remarks: no increase incidence of tumors, Information given is based on data obtained from similar substances.
	Species: Mouse Sex: male Dose: 0, 500, 2000, 8000 ppm Exposure time: 2 years Number of exposures: 6 hr/d, 5 d/wk Remarks: no increase incidence of tumors, Information given is based on data obtained from similar substances.
	Species: Mouse Sex: female Dose: 0, 500, 2000, 8000 ppm Exposure time: 2 years Number of exposures: 6 hr/d, 5 d/wk Remarks: no increase incidence of tumors, Information given is based on data obtained from similar substances.
Reproductive toxicity	
1-Butene	 Species: Rat Sex: male and female Application Route: Inhalation Dose: 0, 500, 2000, 8000 ppm Method: OECD Guideline 422 NOAEL Parent: 8000 ppm NOAEL F1: 8000 ppm
CMR effects	
1-Butene	 Carcinogenicity: Weight of evidence does not support classification as a carcinogen Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Teratogenicity: Animal testing did not show any effects on fetal development. Reproductive toxicity: Animal testing did not show any effects on fertility.
n-Butane	Carcinogenicity: Weight of evidence does not support classification as a carcinogen Mutagenicity: Weight of evidence does not support classification as a germ cell mutagen. Teratogenicity: Not available Reproductive toxicity: Weight of evidence does not support classification for reproductive toxicity
1-BUTENE Further information	: No data available.

Version 2.4

SAFETY DATA SHEET

TION 12: Ecological informa	tion		
Toxicity to fish			
1-Butene	: No data available		
Toxicity to daphnia and other aquatic invertebrates			
1-Butene	: No data available		
Toxicity to algae			
1-Butene	: No data available		
Biodegradability	: This material is expected to be readily biodegradable.		
Elimination information (persis	stence and degradability)		
Bioaccumulation			
1-Butene	 Bioconcentration factor (BCF): 17.8 Method: QSAR modeled data This material is not expected to bioaccumulate. 		
n-Butane	: This material is not expected to bioaccumulate.		
Mobility			
1-Butene	: Medium: Air Method: Calculation, Mackay Level I Fugacity Model Content: 99.99 %		
	: Medium: Water Method: Calculation, Mackay Level I Fugacity Model Content: 0.01 %		
n-Butane	: The product evaporates readily.		
Results of PBT assessment 1-Butene	: Non-classified PBT substance, Non-classified vPvB substance		
n-Butane	: This substance is not considered to be persistent, bioaccumulating and toxic (PBT)., This substance is not considered to be very persistent and very bioaccumulating (vPvB).		
Additional ecological information Ecotoxicology Assessment	: No data available		
Short-term (acute) aquatic haz	zard		
S Number:100000068454	10/15		

BUTENE	SAFETY DATA SHE
sion 2.4	Revision Date 2022-11
1-Butene	: This material is not expected to be harmful to aquatic organisms.
Long-term (chronic) aquatic 1-Butene	hazard : This material is not expected to be harmful to aquatic organisms.
TION 13: Disposal conside	rations
The information in this SDS	pertains only to the product as shipped.
may meet the criteria of a har other State and local regulat regulated components may b	purpose or recycle if possible. This material, if it must be discarded, azardous waste as defined by US EPA under RCRA (40 CFR 261) or ions. Measurement of certain physical properties and analysis for be necessary to make a correct determination. If this material is aste, federal law requires disposal at a licensed hazardous waste
Product	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.
TION 14: Transport information	ation
The shipping descriptions	ation shown here are for bulk shipments only, and may not apply to kages (see regulatory definition).
The shipping descriptions shipments in non-bulk pace Consult the appropriate dom Goods Regulations for additi etc.) Therefore, the information	shown here are for bulk shipments only, and may not apply to
The shipping descriptions shipments in non-bulk pace Consult the appropriate dom Goods Regulations for additi etc.) Therefore, the informati description for the material. bill of lading.	shown here are for bulk shipments only, and may not apply to kages (see regulatory definition). nestic or international mode-specific and quantity-specific Dangerous ional shipping description requirements (e.g., technical name or name tion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and the DEPARTMENT OF TRANSPORTATION)
The shipping descriptions shipments in non-bulk pace Consult the appropriate dom Goods Regulations for additi etc.) Therefore, the informate description for the material. bill of lading. US DOT (UNITED STATES UN1012, BUTYLENE, 2. NON- ODORIZED	shown here are for bulk shipments only, and may not apply to ekages (see regulatory definition). The stic or international mode-specific and quantity-specific Dangerous ional shipping description requirements (e.g., technical name or name tion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and the DEPARTMENT OF TRANSPORTATION) 1 NAL MARITIME DANGEROUS GOODS)
The shipping descriptions shipments in non-bulk pace Consult the appropriate dom Goods Regulations for additi etc.) Therefore, the informate description for the material. bill of lading. US DOT (UNITED STATES UN1012, BUTYLENE, 2. NON- ODORIZED IMO / IMDG (INTERNATION UN1012, BUTYLENE, 2. NON- ODORIZED	shown here are for bulk shipments only, and may not apply to ckages (see regulatory definition). Hestic or international mode-specific and quantity-specific Dangerous tional shipping description requirements (e.g., technical name or name tion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and t DEPARTMENT OF TRANSPORTATION) 1 NAL MARITIME DANGEROUS GOODS) 1, (-80 °C c.c.) R TRANSPORT ASSOCIATION)
The shipping descriptions shipments in non-bulk pace Consult the appropriate dom Goods Regulations for additi etc.) Therefore, the informate description for the material. bill of lading. US DOT (UNITED STATES UN1012, BUTYLENE, 2. NON- ODORIZED IMO / IMDG (INTERNATION UN1012, BUTYLENE, 2. NON- ODORIZED IATA (INTERNATIONAL AII UN1012, BUTYLENE, 2. NON- ODORIZED	shown here are for bulk shipments only, and may not apply to ckages (see regulatory definition). The stic or international mode-specific and quantity-specific Dangerous tional shipping description requirements (e.g., technical name or name tion shown here, may not always agree with the bill of lading shipping Flashpoints for the material may vary slightly between the SDS and t DEPARTMENT OF TRANSPORTATION) 1 NAL MARITIME DANGEROUS GOODS) 1, (-80 °C c.c.) R TRANSPORT ASSOCIATION) 1

1-BUTENE

Version 2.4

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE)) 23,UN1012,1-BUTYLENE, 2.1 NON- ODORIZED ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS) UN1012, 1-BUTYLENE, 2.1 NON- ODORIZED				
Other information	: Butylenes (all isomers), 2G/2PG			
Maritime transport in bulk	Maritime transport in bulk according to IMO instruments			
SECTION 15: Regulatory inform	ation			
National legislation				
SARA 311/312 Hazards	: Flammable (gases, aerosols, liquids, or solids) Gases under pressure			
EPCRA - EMERGENCY PL	EPCRA - EMERGENCY PLANNING COMMUNITY RIGHT - TO – KNOW			
CERCLA Reportable Quantity	: Calculated RQ exceeds reasonably attainable upper limit. 1,3-Butadiene			
SARA 302 Reportable Quantity	: This material does not contain any components with a SARA 302 RQ.			
SARA 302 Threshold Planning Quantity	: This material does not contain any components with a section 302 EHS TPQ.			
SARA 304 Reportable Quantity	: This material does not contain any components with a section 304 EHS RQ.			
SARA 313 Components	: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.			
Clean Air Act	Clean Air Act			
SDS Number:100000068454	12/15			

BUTENE	SAFETY DATA SHEE
ersion 2.4	Revision Date 2022-11-30
Potential Class II C	uct neither contains, nor was manufactured with a Class I or DS as defined by the U.S. Clean Air Act Section 602 (40 CFR . A, App.A + B).
This product does not contain ar Act Section 112 (40 CFR 61).	ny hazardous air pollutants (HAP), as defined by the U.S. Clean Air
Release Prevention (40 CFR 68	ted under the U.S. Clean Air Act Section 112(r) for Accidental .130, Subpart F): 1-Butene - 106-98-9 n-Butane - 106-97-8
Final VOC's (40 CFR 60.489):	ted under the U.S. Clean Air Act Section 111 SOCMI Intermediate of 1-Butene - 106-98-9
US State Regulations	
Pennsylvania Right To Know :	1-Butene - 106-98-9 n-Butane - 106-97-8
California Prop. 65 : Components	WARNING! This product contains a chemical known in the State of California to cause cancer. 1,3-Butadiene 106-99-0
Notification status Europe REACH Switzerland CH INV United States of America (USA) TSCA Canada DSL Australia AICS New Zealand NZIoC Japan ENCS Korea KECI	 This product is in full compliance according to REACH regulation 1907/2006/EC. On the inventory, or in compliance with the inventory On or in compliance with the active portion of the TSCA inventory All components of this product are on the Canadian DSL On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory On the inventory, or in compliance with the inventory Che inventory, or in compliance with the inventory A substance(s) in this product was not registered, notified to be registered, or exempted from registration by CPChem according to K-REACH regulations. Importation or manufacture of this product is still permitted provided the Korean Importer of Record has themselves notified the substance or the exported amount does not exceed the minimum threshold quantity of the non-registered substance(s).
Philippines PICCS China IECSC	On the inventory, or in compliance with the inventoryOn the inventory, or in compliance with the inventory
OS Number:100000068454	13/15

1-BUTENE

Version 2.4

Taiwan TCSI

On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

Revision Date 2022-11-30

Δ

1

0

SECTION 16: Other information

NFPA Classification	:	Health Hazard: 1 Fire Hazard: 4 Reactivity Hazard: 0



Legacy SDS Number : QCHEM019

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

ACGIH	American Conference of	LD50	Lethal Dose 50%
	Government Industrial Hygienists		
AICS	Australia, Inventory of Chemical	LOAEL	Lowest Observed Adverse Effe
	Substances		Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agence
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupatio Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentra
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substan
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recov Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average
Number:100	000069454	1	4/15

1-BUTENE

Version 2.4

Revision Date 2022-11-30

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%	ATE	Acute toxicity estimate

SDS Number:100000068454